




The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

E8DMHL



TECHNICAL CHARACTERISTICS	E8DMHL
MOTOR	
Displacement (cc)	165
Architecture	In Line 2
Bore x Stroke (mm)	50.0 X 42.0
Full throttle operating range (tr/min)	4500-5500
Fuel	Pre-Mix
Fuel consumption (L/h-tr/min)	4.0 L/h @5500 r/min
Lubrication system	Pre-Mixing 2 %
Power system	1 Carburetor
Reduction ratio	6.8 :1
Number of Displacement	-
Maximum Power (Kw)	-
Ignition System	CDI
Gear Ratio	2.08 (27/13)
Steering Control	Tiller hand
Reverse direction	Yes
Trim method (positions)	4
Engine Type	2 Stroke
Start-up	Manual
Max.Prop Shaft Horsepower (Kw)	5.9 (8 hp)
MORE	
Control	Tiller handle
Alternator	40 W (optinal)
Propeller Rotation	Sens Horaire
DIMENSIONS	
Engine Oil Capacity (L)	-
Oil capacity (L)	-
Engine transom height (mm)	L : 582 mm (22.9 in)
Dry weight with propeller (kg)	29



Always wear a helmet, eye protection and protective proper clothing.

CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

