



E60HMHDL/E60HMHDX

«ENDURO» engines, absolute workhorses, offer unrivalled performance for your money and can withstand the toughest usage conditions. All good reasons to explain why YAMAHA Enduro boats for decades.



TECHNICAL CHARACTERISTICS	E60HMHDL	E60HMHDX
MOTOR		
Engine Type	In-line 2	In-line 2
Reduction ratio	6.1 :1	6.1 :1
Start-up	Manual	Manual
Power system	3 Carburetors	3 Carburetors
Lubrication system	Pre-Mixing 2 %	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	25.5 L/h @5500 tr/min	25.5 L/h @5500 tr/min
Fuel	Regular Gasoline	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500	4500-5500
Max.Prop Shaft Horsepower (Kw)	44.1 (60 hp)	44.1 (60 hp)
Bore x Stroke (mm)	72.0 X 69.5	72.0 X 69.5
Architecture	L3	L3
Displacement (cc)	849	849
MORE		
Propeller Rotation	Clockwise	Clockwise
Alternator	80 W	80 W
Control	Tiller handle	Tiller handle
DIMENSIONS		
Engine transom height (mm)	L: 571 mm (22.5 in)	X : 648 mm (25.5 in)
Dry weight with propeller (kg)	105	105

Always wear a helmet, eye protection and protective proper clothing.

CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

